

Prepared By:
Anne Stehno
Utah Fleet Operations
801-619-7242
annestehno@utah.gov

Prepared For:
CLASS 0218 SB DCNG

2013 Chevrolet Silverado 2500HD 2WD Ext Cab 144.2"



2013 Chevrolet Silverado 2500HD 2WD Ext Cab 144.2" Work Truck (CC20753)

CLASS 0218 SB

TRUCK 3/4 TON EXTENDED CAB 4X2 SB DCNG

OPTIONAL EQUIPMENT SUPERSEDES STANDARD EQUIPMENT

Vehicle Report: Table of Contents

VEHICLE INFORMATION	
Selected Model	1
Selected Vehicle Colors	1
Selected Options	1
Aftermarket Options	2
STANDARD EQUIPMENT	
Mechanical	3
Exterior	3
Entertainment	3
Interior	4
Safety	4
TECHNICAL SPECIFICATIONS	
Chassis	5
Vehicle	7
Powertrain	7
Dimensions	8
WARRANTY INFORMATION	
Warranty Information	10

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Vehicle Information

SELECTED MODEL

Code	Description	Front Weight	Rear Weight
CC20753	2013 Chevrolet Silverado 2500HD 2WD Ext Cab 144.2" Work Truck	3352 lbs	2655 lbs

SELECTED VEHICLE COLORS

SELECTED OPTIONS

Code	Description	Front Weight	Rear Weight
E63	PICKUP BOX, FLEETSIDE, (STD)		
Z85	SUSPENSION PACKAGE, HANDLING/TRAILERING, HEAVY-DUTY, includes 35mm twin tube shock absorbers and 36mm front stabilizer bar (STD)		
FE9	EMISSIONS, FEDERAL REQUIREMENTS		
LC8	ENGINE, 6.0L V8 SFI GASEOUS WITH HARDENED VALVES AND VALVE SEATS. OPERATES ON BOTH GASOLINE AND CNG., Not E85 compatible. Running on gasoline (360 hp [268 kW] @ 5400 rpm, 380 lb-ft of torque [515 N-m] @ 4200 rpm), Running on CNG (301 hp [225 kW] @ 5000 rpm, 333 lb-ft of torque [452 N-m] @ 4200 rpm)., (Requires Extended Cab C*20*53 models, (RW1) Bed rail protectors, LPO, (MYD) 6-speed automatic, heavy duty transmission, (E63) Pickup box, Wideside, (FHV) Bi-Fuel Compressed Natural Gas, CNG, fuel system and (KC4) Cooling, external engine oil cooler. Not available with (UY2) trailering wiring provisions. Reference the Engine/Axle page for availability. Not available with LPO's (VBN), (VBP), (VBR), (VPB), (VQG), (VQT), (VZX), (VZZ), (5JY), (SC0) or (PDC) LPO, On The Job Package.)		
MYD	TRANSMISSION, 6-SPEED AUTOMATIC, HEAVY-DUTY, ELECTRONICALLY CONTROLLED, with overdrive and tow/haul mode. Includes Cruise Grade Braking and Powertrain Grade Braking (STD), (Requires (L96) Vortec 6.0L V8 SFI engine or (LC8) 6.0L V8 SFI Gaseous engine.)		
GEH	GVWR, 9500 LBS. (4309 KG), (Requires (L96) Vortec 6.0L V8 SFI engine or (LC8) 6.0L V8 SFI Gaseous engine. Not available on CC20903 or CK20943 models.)		
GT4	REAR AXLE, 3.73 RATIO		
1WT	WORK TRUCK PREFERRED EQUIPMENT GROUP, includes standard equipment		
PYN	WHEELS, 17" (43.2 CM) STEEL, (Includes 17" x 7.5" (43.2 cm x 19.1 cm) steel spare wheel. (STD), Spare not included with (ZW9) pickup box delete unless a spare tire is ordered.)		
QHJ	TIRES, LT245/75R17E ALL-SEASON, BLACKWALL, (STD)		
ZY1	PAINT, SOLID		
AE7	SEATS, FRONT 40/20/40 SPLIT-BENCH, 3-PASSENGER, DRIVER AND FRONT PASSENGER MANUAL RECLINING, with outboard head restraints and center fold-down armrest with storage (STD)		
88B	DARK TITANIUM, CLOTH SEAT TRIM, (Seats are Ebony seating surfaces and Ebony bolsters.)		
		Front Weight	Rear Weight
US8	AUDIO SYSTEM, AM/FM STEREO WITH MP3 COMPATIBLE CD PLAYER, seek-and-scan, digital clock, auto-tone control, Radio Data System (RDS), speed-compensated volume and TheftLock, (Required with (U2K) SiriusXM Satellite Radio.)	2.0	1.0
		Front Weight	Rear Weight
FHV	BI-FUEL DEDICATED COMPRESSED NATURAL GAS CNG SYSTEM, (complete vehicle and system ready) Operates on both gasoline and CNG: Not E85 compatible. CNG tank mounted in forward end of bed., (Requires Extended Cab C*20*53 models, RPO (LC8) 6.0L V8 SFI Gaseous CNG (compressed natural gas) engine, with hardened valves and valve seats and (RW1) Bed rail protectors, LPO.)	113.0	338.0
G80	DIFFERENTIAL, HEAVY-DUTY AUTOMATIC LOCKING REAR, (Included with (Z82) trailering equipment on Retail Orders only.)	0.0	4.0
Z82	TRAILERING EQUIPMENT, HEAVY-DUTY, includes trailering hitch platform and 2.5- inch receiver with 2" adapter, 7-wire harness (harness includes wires for: park lamps, backup lamps, right turn, left turn, electric brake lead, battery and ground) with independent fused trailering circuits mated to a 7-way sealed connector, wiring harness for after-market trailer brake controller (located in the instrument panel harness) and (JL1) integrated trailer brake controller, (Also includes (G80) heavy-duty automatic locking rear differential on Retail Orders only. Not available with (ZW9) pickup box delete or (VF7) rear bumper delete.)		
JL1	TRAILER BRAKE CONTROLLER, INTEGRATED, (With (E63) fleetside pickup box, included and only available with (Z82) heavy-duty trailering equipment. Available as a free flow option with (ZW9) pickup box delete.)	2.0	2.0

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Code	Description		
DL8	MIRRORS, OUTSIDE HEATED POWER-ADJUSTABLE, BLACK, MANUAL-FOLDING, (Included and only available with SEO (5B5) power windows, locks and mirrors.)	2.0	1.0
VK3	LICENSE PLATE FRONT MOUNTING PACKAGE, (will be forced on orders with ship-to states that require a front license plate)	1.0	0.0
RW1	LPO, BED RAIL PROTECTORS, (Included with (PDC) On The Job Package, LPO. Required with (LC8) 6.0L V8 SFI Gaseous CNG (compressed natural gas) engine. Not available with (VQG) Protection Package, LPO or (ZW9) pickup box delete.)	0.0	5.0
AM1	SEAT ADJUSTER, MANUAL LUMBAR CONTROL ON THE DRIVER-SIDE, (Included and only available with (88B) Dark Titanium Cloth seat trim)	3.0	5.0
AU3	DOOR LOCKS, POWER, includes Remote Keyless Entry, (Standard on Crew Cab models. Includes Remote Keyless Entry unless SEO (5B5) power windows, locks and mirrors is ordered)	1.0	0.0
AU0	REMOTE KEYLESS ENTRY, with 2 transmitters and panic button., (Requires SEO (5B5) power windows, locks and mirrors.), Optional on all models when SEO (5B5) power windows, locks and mirrors is ordered		
ASF	AIR BAGS, HEAD CURTAIN SIDE-IMPACT, FRONT OUTBOARD SEATING POSITIONS, with rollover sensor, (Always use safety belts and child restraints. Children are safer when properly secured in a rear seat in the appropriate child restraint. See the Owner's Manual for more information.)	7.0	6.0
AJ7	AIR BAGS, SEAT-MOUNTED SIDE-IMPACT, DRIVER AND RIGHT-FRONT PASSENGER, for thorax and pelvic protection, (Included and only available with (ASF) head curtain side-impact air bags. Always use safety belts and child restraints. Children are safer when properly secured in a rear seat in the appropriate child restraint. See the Owner's Manual for more information.)		
5B5	WINDOWS, LOCKS AND MIRRORS, POWER WITH UPLEVEL DOOR PANELS ON A BASE TRIM LEVEL VEHICLE, Provides power driver and passenger front side windows with uplevel door panels on a base trim level vehicle. Includes RPO (DL8) outside heated power-adjustable manual folding mirrors, RPO (AU3) power door locks and RPO (UQ3) speaker system. C/K***43-53 models include rear door power windows and locks., (Power mirrors can be upgraded to SEO (6P3) camper, power-adjustable glass, manual extendable, heated mirrors. (Remote Keyless Entry becomes optional on all models and SEO (AU0) Remote Keyless Entry must be ordered and priced if desired.)	2.0	2.0

AFTERMARKET OPTIONS

Chev-MatExt	Front Weight	Rear Weight
Floor Mats, Truck, Extended Cab. Option code: AMO.	0	0

All prices and specifications are subject to change without notice. Prices do not include sales tax, vehicle registration fees, finance charges, documentation charges, or other fees required by law. Dealer invoice prices do not include dealer charges, such as advertising charges, that can vary by manufacturer or region.

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Standard Equipment

MECHANICAL

Engine, Vortec 6.0L Variable Valve Timing V8 SFI E85-compatible, FlexFuel capable of running on unleaded or up to 85% ethanol (360 hp [268.4 kW] @ 5400 rpm, 380 lb-ft of torque [513.0 N-m] @ 4200 rpm) with (E63) fleetside pickup box; (322 hp [240.1 kW] @ 4400 rpm, 380 lb-ft of torque [513.0 N-m] @ 4200 rpm) with (ZW9) pickup box delete (Does not include E85 capability with (ZW9) pickup box delete.)

Transmission, 6-speed automatic, heavy-duty, electronically controlled with overdrive and tow/haul mode. Includes Cruise Grade Braking and Powertrain Grade Braking (Requires (L96) Vortec 6.0L V8 SFI engine or (LC8) 6.0L V8 SFI Gaseous engine.)

Rear axle, 3.73 ratio

Suspension Package, Handling/Trailering, heavy-duty includes 35mm twin tube shock absorbers and 36mm front stabilizer bar

Air cleaner, high-capacity

Cooling, auxiliary external transmission oil cooler heavy-duty air-to-oil

Cooling, external engine oil cooler heavy-duty air-to-oil, integral to driver side of radiator tank

Rear wheel drive

Battery, heavy-duty 600 cold-cranking amps, maintenance-free with rundown protection and retained accessory power

Alternator, 125 amps

Frame, fully-boxed, hydroformed front section

Suspension, front independent, torsion bar

Suspension, rear 4+1 multi-leaf springs

Steering, power, recirculating ball

Brakes, 4-wheel antilock, 4-wheel disc

Exhaust aluminized stainless-steel muffler and tailpipe

EXTERIOR

Wheels, 17" (43.2 cm) steel (Includes 17" x 7.5" (43.2 cm x 19.1 cm) steel spare wheel. Spare not included with (ZW9) pickup box delete unless a spare tire is ordered.)

Tires, LT245/75R17E all-season, blackwall

Pickup box, Fleetside

Recovery hooks, front, Black

Tire carrier, outside spare, winch-type mounted under frame at rear (Orders with (ZW9) Pickup box delete will not include a Spare Tire Carrier unless a spare tire is ordered)

Spare tire lock keyed cylinder lock that utilizes same key as ignition and door (Not included when (ZW9) pickup box delete or (VF7) rear bumper delete is ordered.)

Bumper, front chrome includes chrome bumper end caps

Bumper, rear chrome, step-style with pad (Not available with (ZW9) pickup box delete.)

Grille, chrome surround

Headlamps, dual halogen composite with automatic exterior lamp control and flash-to-pass feature

Lamps, dual cargo area lamps

Mirrors, outside manual, Black, manual-folding

Glass, Solar-Ray light-tinted, all windows

Wipers, front intermittent wet-arm with pulse washers

Door handles, Black

ENTERTAINMENT

Audio system, AM/FM stereo with seek-and-scan and digital clock (Not available with (U2K) SiriusXM Satellite Radio.)

SiriusXM Satellite Radio, delete

Audio system feature, speaker system (Included with (5B5) power windows, doors and locks, SEO. Includes 4 speakers on Regular Cab models and 6 speakers on Extended and Crew Cab models.)

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

INTERIOR

Seats, front 40/20/40 split-bench, 3-passenger, driver and front passenger manual reclining with outboard head restraints and center fold-down armrest with storage

Seat trim, Vinyl

Seat, rear bench (folds up), full width, folding, 3-passenger (includes child seat top tether anchor) (Standard with Extended Cab models only)

Floor covering, Black rubberized vinyl

Steering column, Tilt-Wheel, adjustable with brake/transmission shift interlock

Steering wheel includes theft-deterrent locking feature

Instrumentation, analog with speedometer, fuel level, engine temperature, tachometer, voltmeter and oil pressure indicators

Driver Information Center with odometer, trip odometer and message center (monitors numerous systems depending on vehicle equipment level including low fuel, turn signal "on", transmission temperature and oil change notification) (Driver Information Center controls are operated through the trip odometer button unless (UK3) steering wheel mounted audio controls is ordered. On 1LT and 1LZ, includes 8-point compass and outside temperature.)

Warning tones headlamp on, key-in-ignition, driver and passenger buckle up reminder and turn signal on

Windows, fixed, rear access door (Standard with Extended Cab models only)

Cruise control, electronic with set and resume speed, located on steering wheel

Air conditioning, single-zone manual front climate control

Cup holders, front (Also includes rear cupholders on Extended and Crew Cab models)

Power outlets 2 auxiliary instrument panel-mounted with covers, 12-volt

Mirror, inside rearview manual day/night

Visors, driver and front passenger, sliding with clip and passenger side vanity mirror with cover, Opal Gray-colored

Assist handle, front passenger (Also includes rear assist handles in the headliner on Extended and Crew Cab models)

Lighting, interior with dome and reading lights, illuminated entry feature and backlit instrument panel switches

Coat hooks, rear driver and passenger side

SAFETY

StabiliTrak, stability control system with Proactive Roll Avoidance and traction control, includes electronic trailer sway control and hill start assist

Daytime Running Lamps with automatic exterior lamp control

Air bags, frontal, driver and right-front passenger (Always use safety belts and child restraints. Children are safer when properly secured in a rear seat in the appropriate child restraint. See the Owner's Manual for more information.)

OnStar, delete

Tire Pressure Monitor System (does not apply to spare tire)

All specifications are subject to change without notice.

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Technical Specifications

CHASSIS

Weight Information

Trim Curb Weight	6007.00 lbs
Standard Weight - Front	0 lbs
Standard Weight - Rear	0 lbs
Base Trim Weight - Front	3352.00 lbs
Base Trim Weight - Rear	2655.00 lbs
Gross Axle Wt Rating - Front	4400 lbs
Gross Axle Wt Rating - Rear	6200 lbs
Curb Weight - Front	3352 lbs
Curb Weight - Rear	2655 lbs
Option Weight - Front	133.00 lbs
Option Weight - Rear	364.00 lbs
Reserve Axle Capacity - Front	915.00 lbs
Reserve Axle Capacity - Rear	3181.00 lbs
As Spec'd Curb Weight	6504.00 lbs
As Spec'd Payload	2996.00 lbs
Maximum Payload Capacity	3493.00 lbs
Gross Combined Wt Rating	16000 lbs
Gross Axle Weight Rating	10600.00 lbs
Curb Weight	6007.00 lbs
Reserve Axle Capacity	4096.00 lbs
Total Option Weight	497.00 lbs
Payload Weight Front	0 lbs
Payload Weight Rear	0 lbs
Gross Vehicle Weight Rating	9500.00 lbs

Trailer

Dead Weight Hitch - Max Trailer Wt.	5000 lbs
Dead Weight Hitch - Max Tongue Wt.	500 lbs
Wt Distributing Hitch - Max Trailer Wt.	9300 lbs
Wt Distributing Hitch - Max Tongue Wt.	1395 lbs
Maximum Trailering Capacity	17500 lbs

Frame

Frame Type	Hydroformed
Sect Modulus Rails Only	N/A in ³
Frame RBM	N/A N/A
Frame Strength	N/A lbs
Frame Thickness	N/A in

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Suspension

Suspension Type - Front	Independent
Suspension Type - Rear	Multi-Leaf
Spring Capacity - Front	4400 lbs
Spring Capacity - Rear	6200 lbs
Axle Type - Front	Independent
Axle Type - Rear	Semi Floating
Axle Capacity - Front	4400 lbs
Axle Capacity - Rear	6200 lbs
Axle Ratio (:1) - Front	
Axle Ratio (:1) - Rear	3.73
Shock Absorber Diameter - Front	35 mm
Shock Absorber Diameter - Rear	35 mm
Stabilizer Bar Diameter - Front	1.31 in
Stabilizer Bar Diameter - Rear	

Tires

Front Tire Order Code	QHQ
Rear Tire Order Code	QHQ
Spare Tire Order Code	
Front Tire Size	LT245/75R17
Rear Tire Size	LT245/75R17
Spare Tire Size	
Front Tire Capacity	N/A lbs
Rear Tire Capacity	3195 lbs
Spare Tire Capacity	N/A lbs
Revolutions/Mile @ 45 mph - Front	N/A
Revolutions/Mile @ 45 mph - Rear	N/A
Revolutions/Mile @ 45 mph - Spare	N/A

Wheels

Front Wheel Size	17 x -TBD- in
Rear Wheel Size	17 x -TBD- in
Spare Wheel Size	17 x 7.5 in
Front Wheel Material	Steel
Rear Wheel Material	Steel
Spare Wheel Material	Steel

Steering

Steering Type	Pwr
Steering Ratio (:1), Overall	N/A
Steering Ratio (:1), On Center	24.0
Steering Ratio (:1), At Lock	N/A
Turning Diameter - Curb to Curb	47.9 ft
Turning Diameter - Wall to Wall	N/A ft

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Brakes

Brake Type	Pwr
Brake ABS System	4-Wheel
Brake ABS System (Second Line)	
Disc - Front (Yes or)	Yes
Disc - Rear (Yes or)	Yes
Front Brake Rotor Diam x Thickness	13.8 x 1.57 in
Rear Brake Rotor Diam x Thickness	14.17 x 1.34 in
Drum - Rear (Yes or)	
Rear Drum Diam x Width	

Fuel Tank

Fuel Tank Capacity, Approx	36.0 gal
Aux Fuel Tank Capacity, Approx	
Fuel Tank Location	N/A
Aux Fuel Tank Location	

VEHICLE

Tons/yr of CO2 Emissions @ 15K mi/year	N/A
EPA Greenhouse Gas Score	N/A

POWERTRAIN

Transmission

Drivetrain	Rear Wheel Drive
Trans Order Code	MYD
Trans Type	6
Trans Description Cont.	Automatic
Trans Description Cont. Again	
First Gear Ratio (:1)	4.03
Second Gear Ratio (:1)	2.36
Third Gear Ratio (:1)	1.53
Fourth Gear Ratio (:1)	1.15
Fifth Gear Ratio (:1)	0.85
Sixth Gear Ratio (:1)	0.67
Reverse Ratio (:1)	3.06
Clutch Size	
Trans Power Take Off	
Final Drive Axle Ratio (:1)	N/A
Transfer Case Model	
Transfer Case Gear Ratio (:1), High	
Transfer Case Gear Ratio (:1), Low	
Transfer Case Power Take Off	

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Mileage

EPA Fuel Economy Est - Hwy	
Cruising Range - City	0.00 mi
EPA Fuel Economy Est - City	
Fuel Economy Est-Combined	
Cruising Range - Hwy	0.00 mi

Engine

Engine Order Code	LC8
Engine Type	Gas/Natural Gas V8
Displacement	6.0L/366
Fuel System	Electronic Fuel Injection
SAE Net Horsepower @ RPM	360 @ 5400
SAE Net Torque @ RPM	380 @ 4200
Engine Oil Cooler	Yes

Electrical

Cold Cranking Amps @ 0° F (Primary)	600
Cold Cranking Amps @ 0° F (2nd)	
Cold Cranking Amps @ 0° F (3rd)	N/A
Maximum Alternator Capacity (amps)	125

Cooling System

Total Cooling System Capacity	N/A qts
-------------------------------	---------

DIMENSIONS

Interior Dimensions

Passenger Capacity	6
Front Head Room	41.10 in
Front Leg Room	41.30 in
Front Shoulder Room	65.20 in
Front Hip Room	60.30 in
Second Head Room	39.50 in
Second Leg Room	34.40 in
Second Shoulder Room	65.30 in
Second Hip Room	61.80 in

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Exterior Dimensions

Wheelbase	144.20 in
Length, Overall w/o rear bumper	230.60 in
Width, Max w/o mirrors	80.00 in
Height, Overall	77.90 in
Overhang, Front	38.80 in
Overhang, Rear w/o bumper	52.60 in
Front Bumper to Back of Cab	141.40 in
Cab to Axle	41.60 in
Cab to End of Frame	N/A in
Ground to Top of Load Floor	38.20 in
Ground to Top of Frame	N/A in
Frame Width, Rear	N/A in
Ground Clearance, Front	9.80 in
Ground Clearance, Rear	8.60 in
Body Length	0.00 ft
Cab to Body	N/A in

Cargo Area Dimensions

Cargo Box Length @ Floor	78.80 in
Cargo Box Width @ Top, Rear	N/A in
Cargo Box Width @ Floor	62.50 in
Cargo Box Width @ Wheelhousings	50.60 in
Cargo Box (Area) Height	21.00 in
Tailgate Width	61.60 in
Cargo Volume	60.7 ft ³
Ext'd Cab Cargo Volume	N/A ft ³

Report content is based on current data. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Warranty Information

Basic:

3 Years/36,000 Miles

Drivetrain:

5 Years/100,000 Miles

Corrosion:

3 Years/36,000 Miles

Rust-Through

6 Years/100,000 Miles

Roadside Assistance:

5 Years/100,000 Miles

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.