

Prepared By:
Anne Stehno
Utah Fleet Operations
801-619-7242
annestehno@utah.gov

Prepared For:
CLASS 4910 DCNG

2013 Chevrolet Express Cargo Van RWD 2500 135"



2013 Chevrolet Express Cargo Van RWD 2500 135" (CG23405)

CLASS 4910

VAN CARGO FULLSIZE DCNG

OPTIONAL EQUIPMENT SUPERSEDES STANDARD EQUIPMENT

Vehicle Report: Table of Contents

| VEHICLE INFORMATION | |
|--------------------------|----|
| Selected Model | 1 |
| Selected Vehicle Colors | 1 |
| Selected Options | 1 |
| STANDARD EQUIPMENT | |
| Mechanical | 3 |
| Exterior | 9 |
| Entertainment | 3 |
| Interior | 3 |
| Safety | 4 |
| TECHNICAL SPECIFICATIONS | |
| Chassis | 5 |
| Vehicle | 7 |
| Powertrain | 7 |
| Dimensions | 8 |
| Exterior | 9 |
| WARRANTY INFORMATION | |
| Warranty Information | 10 |

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Vehicle Information

SELECTED MODEL

| Code | Description | Front Weight | Rear Weight |
|---------|--|--------------|-------------|
| CG23405 | 2013 Chevrolet Express Cargo Van RWD 2500 135" | 2886 lbs | 2405 lbs |

SELECTED VEHICLE COLORS

SELECTED OPTIONS

| Code | Description | Front Weight | Rear Weight |
|---------------------|--|--------------------|-------------|
| ZW9 | BODY, STANDARD, (STD) | | |
| FE9 | EMISSIONS, FEDERAL REQUIREMENTS | | |
| Front Weight | | Rear Weight | |
| LC8 | ENGINE, 6.0L V8 SFI GASEOUS, (279 hp [208.0 kW] @ 4700 rpm, 320 lb-ft of torque [432.0 N-m] @ 4400) with hardened valves and valve seats Includes external engine oil cooler., (Requires CG23405, CG23705, CG33405 or CG33705 models and (FHZ) Dedicated Compressed Natural Gas (CNG) system. Reference the Engine/Axle page for availability.) | 6.0 | 8.0 |
| MYD | TRANSMISSION, 6-SPEED AUTOMATIC, HEAVY-DUTY, ELECTRONICALLY CONTROLLED, with overdrive tow/haul mode and internal transmission oil cooler (STD), (Standard on CG23405, CG23705, CG33405 and CG33705 models. Requires (L20) Vortec 4.8L V8 SFI FlexFuel engine or (L96) Vortec 6.0L V8 SFI FlexFuel engine or (LC8) Gaseous 6.0L V8 SFI engine. Reference the Engine/Axle page for availability.) | | |
| GU6 | REAR AXLE, 3.42 RATIO, (Standard on CG13405, CH13405, CG23405, CG23705, CG33405 and CG33705 models. Required with (LU3) Vortec 4.3L V6 MFI engine, (L20) Vortec 4.8L V8 SFI FlexFuel engine, (L96) Vortec 6.0L V8 SFI FlexFuel or (LC8) Gaseous 6.0L V8 SFI engine. Available with (LMF) Vortec 5.3L V8 SFI FlexFuel engine. Reference the Engine/Axle page for availability.) | | |
| E24 | DOOR, SWING-OUT PASSENGER-SIDE, 60/40 SPLIT, (STD) | | |
| 1WT | PREFERRED EQUIPMENT GROUP, includes Standard Equipment | | |
| ZX9 | TIRE, SPARE DELETE, Not available with (E26) swing-out driver-side door. Required with (FHZ) Dedicated Compressed Natural Gas (CNG) system., (Jack is not included. | | |
| ZY1 | PAINT, SOLID | | |
| Front Weight | | Rear Weight | |
| AS5 | SEATS, FRONT BUCKET WITH CUSTOM CLOTH TRIM, head restraints and inboard armrests Includes (BA3) console with swing-out storage bin., (Requires (**G) interior trim. | 5.0 | 1.0 |
| 93G | MEDIUM PEWTER, CUSTOM CLOTH SEAT TRIM | | |
| ZX2 | SEATING ARRANGEMENT, DRIVER AND FRONT PASSENGER HIGH-BACK BUCKETS, with head restraints and vinyl or cloth trim (STD) | | |
| Front Weight | | Rear Weight | |
| C60 | AIR CONDITIONING, SINGLE-ZONE MANUAL, (STD) | 41.0 | -3.0 |
| Front Weight | | Rear Weight | |
| U1C | AUDIO SYSTEM, AM/FM STEREO WITH CD PLAYER, seek-and-scan, digital clock, TheftLock, random select and 2 front door speakers | 3.0 | 1.0 |
| PDN | POWER PACKAGE, (Includes (ZQ2) Convenience Package and (DE5) outside heated, power-adjustable, Black mirrors., Included with (PCH) Hotel Shuttle Package. Not available with (PRP) Express Access, (YF2) Ambulance Package or (R6G) air conditioning delete.) | | |
| ZQ2 | CONVENIENCE PACKAGE, POWER WINDOWS AND DOOR LOCKS, (Includes (A31) power windows and (AU3) power door locks., Included with (PDN) Power Package, (PRP) Express Access or (PCH) Hotel Shuttle Package., NOTE: Does not include (ATG) Remote Keyless Entry. (ATG) Remote Keyless Entry must be ordered separately.) | 5.0 | 5.0 |
| ZQ3 | CONVENIENCE PACKAGE, TILT-WHEEL AND (K34) CRUISE CONTROL, (Included with (PCH) Hotel Shuttle Package.) | 6.0 | 0.0 |
| V10 | COLD CLIMATE PACKAGE, includes (K05) engine block heater | | |

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

| Code | Description | | |
|------|--|-------|-------|
| K05 | ENGINE BLOCK HEATER, (Included and only available with (V10) Cold Climate Package which requires (LU3) Vortec 4.3L V6 MFI engine, (LMF) Vortec 5.3L V8 SFI FlexFuel engine, (L20) Vortec 4.8L V8 SFI engine, (L96) Vortec 6.0L V8 SFI FlexFuel engine or (LC8) Gaseous 6.0L V8 SFI engine.) | 1.0 | 0.0 |
| FHZ | DEDICATED COMPRESSED NATURAL GAS (CNG) SYSTEM, (complete vehicle and system ready) Includes (UFM) 3-tank configuration fuel system. May upgrade with available (UFP) 4-tank configuration fuel system., (Requires (LC8) Gaseous 6.0L V8 SFI engine, (V10) Cold Climate Package, (ZX9) spare tire delete and (Z82) trailering equipment. Not available with (C69) rear air conditioning or (C36) rear auxiliary heater.) | | |
| Z82 | TRAILERING EQUIPMENT, HEAVY-DUTY, includes trailering hitch platform and 7-pin sealed connector (Includes (UY7) 7-lead trailer wiring harness., Required with (FHZ) Dedicated Compressed Natural Gas (CNG) system.) | -44.0 | 94.0 |
| UY7 | TRAILER WIRING, 7-PIN SEALED CONNECTOR, (Included with (Z82) heavy-duty trailering equipment.) | -2.0 | 3.0 |
| UFM | FUEL TANK, 3-TANK CONFIGURATION FUEL SYSTEM, All tanks are mounted under body., (Requires (FHZ) Dedicated Compressed Natural Gas (CNG) system. May be upgraded to (UFP) 4-tank configuration fuel system. | 10.0 | 496.0 |
| DE5 | MIRRORS, OUTSIDE HEATED POWER-ADJUSTABLE, BLACK, MANUAL-FOLDING, (Requires (ZQ2) Convenience Package. Included with (PCR) Express Access Plus Package or (PDN) Power Package. Not available with (R6G) air conditioning delete.) | 4.0 | 0.0 |
| A12 | GLASS, FIXED REAR DOORS WINDOWS, (Included and only available when (ZW*) is ordered. Included with (YF2) Ambulance Package) | | |
| ZW2 | GLASS, FIXED REAR DOORS, (May upgrade fixed glass to swing-out glass, see (A18) rear cargo door windows swing-out glass. Not available with (PCH) Hotel Shuttle Package.) | 0.0 | 11.0 |
| BA3 | CONSOLE, ENGINE COVER WITH SWING-OUT STORAGE BIN, (Included with (AS5) front bucket seats with Custom Cloth.) | 2.0 | 1.0 |
| U80 | COMPASS, 8-POINT DIGITAL LOCATED IN THE DRIVER INFORMATION CENTER, (Included and only available with (TR9) auxiliary lighting.) | | |
| A31 | WINDOWS, POWER, (Included and only available with (ZQ2) Convenience Package.) | | |
| AU3 | DOOR LOCKS, POWER WITH LOCK-OUT PROTECTION, (Included with (ZQ2) Convenience Package or (PRP) Express Access., NOTE: Does not include (ATG) Remote Keyless Entry. (ATG) Remote Keyless Entry must be ordered separately.) | 1.0 | 1.0 |
| ATG | REMOTE KEYLESS ENTRY, with 2 transmitters and remote panic button, (Requires (AU3) power door locks. Included with (PRP) Express Access.) | | |
| K34 | CRUISE CONTROL, (Included and only available with (ZQ3) Convenience Package, (PCH) Hotel Shuttle Package or (YF2) Ambulance Package.) | | |
| D31 | MIRROR, INSIDE REARVIEW MANUAL DAY/NIGHT, (Included with (ZW*) Glass Packages or (UVC) Rear Vision Camera when (UYS) Audio system with navigation is not ordered.) | | |
| TR9 | LIGHTING, AUXILIARY, with reading and underhood lights Includes (U80) 8-point digital compass., (Standard on CG13405 and CH13405 models. Included with (PCR) Express Access Plus Package. Not available with (YF2) Ambulance Package.) | 1.0 | 1.0 |
| VLW | LPO, BULKHEAD DIVIDER WITH DOOR, (Not available with (VLP) Bulkhead divider, LPO, (R7T/R7Q) commercial customer bin GM Business Choice Upfit or (PRP) Express Access.) | 50.0 | 41.0 |
| ASF | AIR BAGS, HEAD/SIDE-CURTAIN, (Standard on CG13405 and CH13405 models. Requires (AK5) driver and right-front passenger air bags and (TR9) auxiliary lighting. Not available with (AJ3) driver-side only frontal air bag and SEO option (5L3) interior trim panels., Always use safety belts and the correct child restraints. Children are safer when properly secured in a rear seat in the appropriate child restraint. See the Owner's Manual for more information.) | 11.0 | 4.0 |

All prices and specifications are subject to change without notice. Prices do not include sales tax, vehicle registration fees, finance charges, documentation charges, or other fees required by law. Dealer invoice prices do not include dealer charges, such as advertising charges, that can vary by manufacturer or region.

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Standard Equipment

MECHANICAL

Engine, Vortec 4.8L V8 SFI FlexFuel (280 hp [208.8 kW] @ 5200 rpm, 295 lb-ft of torque [398.3 N-m] @ 4600 rpm) (Includes external engine oil cooler. Standard on CG23405, CG23705, CG33405 and CG33705 models. Reference the Engine/Axle page for availability.)

Transmission, 6-speed automatic, heavy-duty, electronically controlled with overdrive tow/haul mode and internal transmission oil cooler (Standard on CG23405, CG23705, CG33405 and CG33705 models. Requires (L20) Vortec 4.8L V8 SFI FlexFuel engine or (L96) Vortec 6.0L V8 SFI FlexFuel engine or (LC8) Gaseous 6.0L V8 SFI engine. Reference the Engine/Axle page for availability.)

Rear axle, 3.42 ratio (Standard on CG13405, CH13405, CG23405, CG23705, CG33405 and CG33705 models. Required with (LU3) Vortec 4.3L V6 MFI engine, (L20) Vortec 4.8L V8 SFI FlexFuel engine, (L96) Vortec 6.0L V8 SFI FlexFuel or (LC8) Gaseous 6.0L V8 SFI engine. Available with (LMF) Vortec 5.3L V8 SFI FlexFuel engine. Reference the Engine/Axle page for availability.)

Body, standard

Transmission oil cooler, external (Included and only available with (L20) Vortec 4.8L V8 SFI FlexFuel engine or (L96) Vortec 6.0L V8 SFI FlexFuel engine.)

Rear wheel drive

Battery, 600 cold-cranking amps, maintenance-free with rundown protection and retained accessory power

Alternator, 105 amps (Not available with CG13405 or CH13405 models.)

Frame, full-length box ladder-type

GVWR, 8600 lbs. (3901 kg) (Standard on CG23405 or CG23705 models. Reference the Engine/Axle page for availability.)

Suspension, front independent with coil springs and stabilizer bar (Requires CG13405, CG23405, CG23705, CG33405 and CG33705 models.)

Suspension, rear hypoid drive axle with multi-leaf springs

Steering, power

Brakes, 4-wheel antilock, 4-wheel disc

Fuel tank capacity, mid-frame and approximately 31 gallons (117.3L)

Exhaust, aluminized stainless-steel muffler and tailpipe

EXTERIOR

Wheels, 4 - 16" x 6.5" (40.6 cm x 16.5 cm) steel includes Gray center caps and steel spare (Standard on CG23405, CG23705, CG33405 and CG33705 models.)

Tires, front LT245/75R16E all-season, blackwall (Standard on the CG23405, CG23705, CG33405 and CG33705 models.)

Tires, rear LT245/75R16E all-season, blackwall (Standard on the CG23405, CG23705, CG33405 and CG33705 models.)

Tire, spare LT245/75R16E all-season, blackwall located at rear underbody of vehicle (Standard on the CG23405, CG23705, CG33405 and CG33705 models.)

Door, swing-out passenger-side, 60/40 split

Bumpers, front and rear painted Black with step-pad (Deleted when (ZR7) Chrome Appearance Package is ordered.)

Grille, Black composite with single rectangular halogen headlamps (Not available with (ZR7) Chrome Appearance Package.)

Headlamps, single halogen (Not available with (ZR7) Chrome Appearance Package.)

Mirrors, outside manual, Black

Glass, Solar-Ray light-tinted, all windows

Wipers, front intermittent wet-arm with pulse washers

License plate kit, front

ENTERTAINMENT

Audio system, radio provisions only. Includes alarm warning chimes, radio wiring harness, radio antenna and 2 front door speakers

INTERIOR

Seats, front bucket with vinyl trim and outboard head restraints, includes inboard armrests. (Requires (**W) interior trim.)

Seating arrangement, driver and front passenger high-back buckets with head restraints and vinyl or cloth trim

Air conditioning, single-zone manual

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Console, engine cover with open storage bin

Floor covering, full-length Black rubberized-vinyl (Not available with (YF2) Ambulance Package or (RFM) rear floor covering delete.)

Steering wheel, steel sleeve column with theft-deterrent locking feature, Black

Instrumentation, analog with speedometer, odometer with trip odometer, fuel level, voltmeter, engine temperature and oil pressure

Oil life monitor

Warning tones, headlamp on and key-in-ignition

Driver Information Center includes fuel range, average speed, oil life, tire pressure monitoring, fuel used, ice warning, engine hours, average fuel economy, tachometer, and maintenance reminders. Compass and outside temperature available if equipped. (When (FHZ) Dedicated Compressed Natural Gas (CNG) system is ordered, includes average speed, oil life, tire pressure monitoring, ice warning, engine hours, tachometer and maintenance reminders. Compass and outside temperature available if equipped.)

Tow/haul mode selector, instrument panel-mounted

Theft-deterrent system, vehicle, PASS-Key III

Defogger, side windows

Cup holders, 3 on the engine console cover

Power outlets, 2 auxiliary on engine console cover with covers, 12-volt

Trim panels, hinged rear side doors and hinged rear doors

Headliner, cloth, over driver and passenger

Visors, driver and front passenger, cloth, padded

Assist handle, front passenger

Lighting, interior with 2 dome lights, defeat switch and door handle-activated switches

SAFETY

Brake/transmission shift interlock, for automatic transmissions

StabiliTrak, traction assistance and vehicle stability enhancement system

Door beams, steel-side

Daytime Running Lamps

Air bags, frontal, driver and right-front passenger (Includes passenger-side air bag deactivation switch on models CG23405, CG23705, CG33405 and CG33705. Not available with (ZX1) driver only high-back bucket seat or (AJ3) driver-side only frontal air bag. Always use safety belts and the correct child restraints. Children are safer when properly secured in a rear seat in the appropriate child restraint. See the Owner's Manual for more information.)

Air bag deactivation switch, frontal, passenger-side (Requires (C6P) 8600 lbs. (3901 kg) GVWR or (C6Y) 9600 lbs. (4354 kg) GVWR. Always use safety belts and the correct child restraints. Children are safer when properly secured in a rear seat in the appropriate child restraint. See the Owner's Manual for more information.)

Tire Pressure Monitoring System (does not apply to spare tires)

All specifications are subject to change without notice.

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Technical Specifications

CHASSIS

Weight Information

| | |
|-------------------------------|-------------|
| Trim Curb Weight | 5291.00 lbs |
| Standard Weight - Front | 0 lbs |
| Standard Weight - Rear | 0 lbs |
| Base Trim Weight - Front | 2886.00 lbs |
| Base Trim Weight - Rear | 2405.00 lbs |
| Gross Axle Wt Rating - Front | 4300 lbs |
| Gross Axle Wt Rating - Rear | 5360 lbs |
| Curb Weight - Front | 2886 lbs |
| Curb Weight - Rear | 2405 lbs |
| Option Weight - Front | 99.00 lbs |
| Option Weight - Rear | 664.00 lbs |
| Reserve Axle Capacity - Front | 1315.00 lbs |
| Reserve Axle Capacity - Rear | 2291.00 lbs |
| As Spec'd Curb Weight | 6054.00 lbs |
| As Spec'd Payload | 2546.00 lbs |
| Maximum Payload Capacity | 3309.00 lbs |
| Gross Combined Wt Rating | 16000 lbs |
| Gross Axle Weight Rating | 9660.00 lbs |
| Curb Weight | 5291.00 lbs |
| Reserve Axle Capacity | 3606.00 lbs |
| Total Option Weight | 763.00 lbs |
| Payload Weight Front | 0 lbs |
| Payload Weight Rear | 0 lbs |
| Gross Vehicle Weight Rating | 8600.00 lbs |

Trailer

| | |
|---|-----------|
| Dead Weight Hitch - Max Trailer Wt. | 5000 lbs |
| Dead Weight Hitch - Max Tongue Wt. | 500 lbs |
| Wt Distributing Hitch - Max Trailer Wt. | 9900 lbs |
| Wt Distributing Hitch - Max Tongue Wt. | 1485 lbs |
| Maximum Trailering Capacity | 10000 lbs |

Frame

| | |
|-------------------------|---------------------|
| Frame Type | Ladder |
| Sect Modulus Rails Only | N/A in ³ |
| Frame RBM | N/A N/A |
| Frame Strength | N/A lbs |
| Frame Thickness | N/A in |

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Suspension

| | |
|---------------------------------|-------------------|
| Suspension Type - Front | Coil Spring |
| Suspension Type - Rear | Hypoid Multi-Leaf |
| Spring Capacity - Front | 4100 lbs |
| Spring Capacity - Rear | 5360 lbs |
| Axle Type - Front | Independent |
| Axle Type - Rear | Semi-Floating |
| Axle Capacity - Front | 4100 lbs |
| Axle Capacity - Rear | 5360 lbs |
| Axle Ratio (:1) - Front | |
| Axle Ratio (:1) - Rear | 3.42 |
| Shock Absorber Diameter - Front | N/A mm |
| Shock Absorber Diameter - Rear | N/A mm |
| Stabilizer Bar Diameter - Front | 1.38 in |
| Stabilizer Bar Diameter - Rear | |

Tires

| | |
|-----------------------------------|--------------|
| Front Tire Order Code | XLP |
| Rear Tire Order Code | YLP |
| Spare Tire Order Code | |
| Front Tire Size | LT245/75R16E |
| Rear Tire Size | LT245/75R16E |
| Spare Tire Size | |
| Front Tire Capacity | 2205 lbs |
| Rear Tire Capacity | 3042 lbs |
| Spare Tire Capacity | |
| Revolutions/Mile @ 45 mph - Front | N/A |
| Revolutions/Mile @ 45 mph - Rear | N/A |
| Revolutions/Mile @ 45 mph - Spare | |

Wheels

| | |
|----------------------|-------------|
| Front Wheel Size | 16 x 6.5 in |
| Rear Wheel Size | 16 x 6.5 in |
| Spare Wheel Size | |
| Front Wheel Material | Steel |
| Rear Wheel Material | Steel |
| Spare Wheel Material | |

Steering

| | |
|---------------------------------|---------|
| Steering Type | Pwr |
| Steering Ratio (:1), Overall | N/A |
| Steering Ratio (:1), On Center | 17.2 |
| Steering Ratio (:1), At Lock | 17.2 |
| Turning Diameter - Curb to Curb | 49.2 ft |
| Turning Diameter - Wall to Wall | N/A ft |

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Brakes

| | |
|------------------------------------|---------------|
| Brake Type | Pwr |
| Brake ABS System | 4-Wheel |
| Brake ABS System (Second Line) | |
| Disc - Front (Yes or) | Yes |
| Disc - Rear (Yes or) | Yes |
| Front Brake Rotor Diam x Thickness | 12.8 x 1.5 in |
| Rear Brake Rotor Diam x Thickness | 13.0 x 1.1 in |
| Drum - Rear (Yes or) | |
| Rear Drum Diam x Width | |

Fuel Tank

| | |
|--------------------------------|------------|
| Fuel Tank Capacity, Approx | 31.0 gal |
| Aux Fuel Tank Capacity, Approx | 15.8 gal |
| Fuel Tank Location | Under-body |
| Aux Fuel Tank Location | |

VEHICLE**Emissions**

| | |
|--|-----|
| Tons/yr of CO2 Emissions @ 15K mi/year | N/A |
| EPA Greenhouse Gas Score | N/A |

Vehicle

| | |
|----------------|----------------|
| Rear Door Type | Dual Swing-out |
|----------------|----------------|

POWERTRAIN**Transmission**

| | |
|-------------------------------------|------------------|
| Drivetrain | Rear Wheel Drive |
| Trans Order Code | MYD |
| Trans Type | 6 |
| Trans Description Cont. | Automatic |
| Trans Description Cont. Again | |
| First Gear Ratio (:1) | 4.03 |
| Second Gear Ratio (:1) | 2.36 |
| Third Gear Ratio (:1) | 1.53 |
| Fourth Gear Ratio (:1) | 1.15 |
| Fifth Gear Ratio (:1) | 0.85 |
| Sixth Gear Ratio (:1) | 0.67 |
| Reverse Ratio (:1) | 3.06 |
| Clutch Size | |
| Trans Power Take Off | |
| Final Drive Axle Ratio (:1) | N/A |
| Transfer Case Model | |
| Transfer Case Gear Ratio (:1), High | |
| Transfer Case Gear Ratio (:1), Low | |
| Transfer Case Power Take Off | |

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Mileage

| | |
|-----------------------------|---------|
| EPA Fuel Economy Est - Hwy | N/A MPG |
| Cruising Range - City | N/A mi |
| EPA Fuel Economy Est - City | N/A MPG |
| Fuel Economy Est-Combined | N/A MPG |
| Cruising Range - Hwy | N/A mi |

Engine

| | |
|--------------------------|---------------------------|
| Engine Order Code | LC8 |
| Engine Type | Compressed Natural Gas V8 |
| Displacement | 6.0L/364 |
| Fuel System | Electronic Fuel Injection |
| SAE Net Horsepower @ RPM | 282 @ 4800 |
| SAE Net Torque @ RPM | 320 @ 4400 |
| Engine Oil Cooler | Yes |

Electrical

| | |
|-------------------------------------|-----|
| Cold Cranking Amps @ 0° F (Primary) | 600 |
| Cold Cranking Amps @ 0° F (2nd) | |
| Cold Cranking Amps @ 0° F (3rd) | N/A |
| Maximum Alternator Capacity (amps) | 105 |

Cooling System

| | |
|-------------------------------|---------|
| Total Cooling System Capacity | N/A qts |
|-------------------------------|---------|

DIMENSIONS

Interior Dimensions

| | |
|----------------------|----------|
| Passenger Capacity | 2 |
| Front Head Room | 39.80 in |
| Front Leg Room | 41.30 in |
| Front Shoulder Room | 68.80 in |
| Front Hip Room | 65.50 in |
| Second Head Room | N/A in |
| Second Leg Room | N/A in |
| Second Shoulder Room | N/A in |
| Second Hip Room | N/A in |

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Exterior Dimensions

| | |
|---------------------------------|-----------|
| Wheelbase | 135.00 in |
| Length, Overall w/o rear bumper | N/A in |
| Length, Overall w/rear bumper | 224.10 in |
| Width, Max w/o mirrors | 79.20 in |
| Height, Overall | 81.50 in |
| Overhang, Front | 39.70 in |
| Overhang, Rear w/o bumper | N/A in |
| Front Bumper to Back of Cab | N/A in |
| Cab to Axle | N/A in |
| Cab to End of Frame | N/A in |
| Ground to Top of Load Floor | 27.80 in |
| Ground to Top of Frame | N/A in |
| Frame Width, Rear | N/A in |
| Ground Clearance, Front | 11.00 in |
| Ground Clearance, Rear | 7.10 in |
| Body Length | 0.00 ft |
| Rear Door Opening Height | 49.40 in |
| Rear Door Opening Width | 57.00 in |
| Side Door Opening Height | 47.90 in |
| Side Door Opening Width | 44.10 in |
| Step Up Height - Front | 20.30 in |
| Step Up Height - Side | 20.80 in |
| Cab to Body | N/A in |

Cargo Area Dimensions

| | |
|--------------------------------------|-----------------------|
| Cargo Box Length @ Floor | N/A in |
| Cargo Area Length @ Floor to Console | 153.60 in |
| Cargo Area Length @ Floor to Seat 1 | 124.60 in |
| Cargo Box Width @ Top, Rear | N/A in |
| Cargo Area Width @ Beltline | N/A in |
| Cargo Box Width @ Floor | N/A in |
| Cargo Box Width @ Wheelhousings | 52.70 in |
| Cargo Box (Area) Height | 52.90 in |
| Tailgate Width | N/A in |
| Cargo Volume | 239.7 ft ³ |
| Ext'd Cab Cargo Volume | N/A ft ³ |

EXTERIOR

Side Door Type

Swing-out

Report content is based on current data. Any performance-related calculations are offered solely as guidelines. Actual unit performance will depend on your operating conditions.

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.

Warranty Information

Basic:

3 Years/36,000 Miles

Drivetrain:

5 Years/100,000 Miles

Corrosion:

3 Years/36,000 Miles

Rust-Through

6 Years/100,000 Miles

Roadside Assistance:

5 Years/100,000 Miles

carbookfleetedition



Warning! Configuration incomplete or configuration logic disabled for subject vehicle(s). Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes, and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos do not represent actual vehicles or exact configurations.

Chrome Carbook Fleet Edition™. Report content is based on data version 2533, current as of 12/16/2012 at 00:13 AM. All contents Copyright © 1986-2007 Chrome Systems Incorporated. All rights reserved.